

VKIN300

UPTO300KG/HR



TECHNICAL SPECIFICATIONS

- Up to 300kg/hr
- Lifting mechanism cycle up to 33 lifts/hr
- Skid dimension front load 7' 7" W x 34' 5/16" L
- Skid dimension side load 7' 7" W x 30'
- Shredding of waste 35mm, up to 80 % volume reduction
- Efficacy of 6 log 10 reduction
- Electricity is the only energy required
- 20kW (avg), 30 kWh (peak) power consumption
- ZERO emissions O3 converted back to O2
- Designed and built for 20 + year service
- Operator and staff safety is a priority
- Waste is treated at room temperature requiring no heat, steam or chemicals
- Premium stainless-steel construction
- Single shaft hardened steel medical waste shredder
- Separate high grade ozone production skid
- Rotary screw robust heavy duty air compressor / dryer
- Oxygen generator (Up to 95% oxygen concentration)
- Microfluidic platform technology air cooled ozone generators
- CE and CSA certified for international markets
- Available in 50 Hz or 60 Hz countries
- Online and remote login support worldwide

Separate Ozone
Skid with
Air Compressor



- ✓ Compact Design Ideal for Waste Treatment in Smaller Facilities
- ✓ Available in Multiple Configurations

